








RoHS

Poles	01P	02P	03P	04P	05P	06P	07P	08P	09P	10P	12P
Dim P	---	2.54	5.08	7.62	10.16	12.70	15.24	17.78	20.32	22.86	27.94
Dim L	3.96	6.50	9.04	11.58	14.12	16.66	19.20	21.74	24.28	26.82	31.90



P.C.B.LAYOUT

(1,2,3,4,5....12POS AVAIL)



SCHEMATIC(TYP.)

HOW TO ORDER/订购


MDSL-xxP-xxx-xxx

- Customer Request/其他要求
- G:Convex bottom F:Flat bottom/针脚类型
- R:Red, B:Blue, K:Black/颜色
- No.of poles:01~12P
- L:平柄
- Model/型号系列

A1.1	DWG.REL	2020.6.18	LM	YZG
REV.	DESCRIPTION	DATE	DRAWN	APPROVED

未注公差/General tolerances(mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50



Specifications/性能说明

- Contact Rating/额定电流
 - Switching.....25mA,24VDC,
 - Non-Switchin.....100mA,50VDC
- Contact Resistance/接触电阻
 - Initial/初始值.....50mΩ Max ,
 - After Life Test/测试后.....100mΩ Max
- Operating Force/拨动力.....1000g Max
- Stroke/拨动行程.....1.8mm
- Electrical Life/电气寿命.....3000 cycles
- Operation Temperature/使用温度.....-20℃ to +70℃
- Storage Temperature/存储温度.....-40℃ to +85℃

Soldering Information/焊接

Keep all switch contacts in their "off" position for all operations/在所有操作过程前，请保持开关在“off位置”。

- Hand Soldering/手工焊

Soldering iron 30W or under at 320℃ for 3 sec. max.

使用30瓦烙铁控制温度在320℃，焊接时间3秒内。

- Wave Soldering/波峰焊

Rencommended Solder Temperature at 260℃ max. 5 seconds for IC type/焊锡温度260℃，3~5秒钟。

- PACKING/包装资料

All DIP Switches are shipped in standar IC tube.

以上产品皆以IC管形式包装。

5	Terminal&Movable Contact/端子	Copper/磷青铜	Gold Plated/镀金
4	Tape Sealed/底部密封	Polyester Film	Black/黑色
3	Base/内芯	PBT UL94V-0	Black/黑色
2	Cover/外壳	PBT UL94V-0	Red/Blue/Black
1	Button/拨柄	PBT UL94V-0	White/白色
ITEM	NAME OF PART	MATERIAL	NOTES

PROJECTION		NAME	MDSL-xxP-xxx
UNITS	mm		
SHEET SIZE	A4	SERIES	MDS series
DRAWING TYPE			
SHEET	1 OF 1		
SCALE	1:1		
DRAWING NO.			



宁波市米奇电子有限责任公司
NINGBO MIQI ELECTRONICS CO., LTD